

ISSN: 2582-7219



International Journal of Multidisciplinary Research in Science, Engineering and Technology

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.206

Volume 8, Issue 6, June 2025

DOI:10.15680/IJMRSET.2025.0806167

ISSN: 2582-7219 | www.ijmrset.com | Impact Factor: 8.206 | ESTD Year: 2018 |



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

Active Balancing of Lithium Ion Battery

Yash Vandre, Rushikesh Tinde, Swasti Joshi, Prafulla Londhe

Department of Electronics and Telecommunication, Sinhgad Institute of Technology and Science, Narhe, Pune, India

ABSTRACT: Lithium-ion battery packs, widely used in electric vehicles and portable electronics, require effective cell balancing to maximize performance, lifespan, and safety. Due to inherent manufacturing differences, individual cells in a battery pack can develop voltage imbalances during charging and discharging cycles. This paper presents an active balancing system that redistributes energy from higher-charged cells to lower-charged ones using bidirectional converters. Unlike passive balancing, which dissipates excess energy as heat, active balancing improves overall efficiency by conserving and reallocating energy. The proposed system enhances state-of-charge (SOC) uniformity across cells, reduces thermal stress, and supports long-term battery health. Simulation and experimental results demonstrate significant improvements in energy utilization and balance speed compared to traditional methods.

KEYWORDS: Lithium-ion battery, Active cell balancing, State of charge (SOC), Bidirectional converter and Monitoring.

I. INTRODUCTION

Battery packs may consist of a very large number of cells stacked in series for higher voltage and parallelly for higher capacity and higher output current. Each individual cell needs to be maintained to safely operate in optimal range of temperature and voltage. For this a significant role is played by the BMS. Not only that, it performs various other functions such as SOH (State of Health), SOC (State of Charge), Cell Balance, network and information storage and transfer, etc. It is a real time system and most of the tasks are carried out simultaneously.

It is desired that in the battery pack all the cells must be of the same model manufacturer, must have the same terminal voltage, cell capacity, power output and same internal chemistry. However, it is not always fulfilled due to external factors. As soon as the battery charges – discharges, the cells inside battery packs charge to imbalance and thus inconsistency increases. This improper balance if not corrected for consecutive load times, leads to a reduced life and efficiency of a cell and thus the whole pack.

Batteries being one of the most critical and expensive components of any electric driven transportation vehicle, it becomes very important to take considerable care in order to ensure reliability and safety. The BMS used in the EV's is very sophisticated as it handles various critical tasks simultaneously and accurately. Amongst various functions performed, the cell balancing is the most pivotal task of a BMS. When any one cell in the battery pack exceeds the Start Balancing voltage, the BMS will begin the balancing algorithm for all cells. The BMS will look for the lowest cell, then place a load on all cells which are more than the maximum difference in voltage above the lowest cell.

RELEVANCE

Active balancing in lithium-ion battery cells is an advanced technique for managing the charge of individual cells within a battery pack. It's particularly useful in applications like electric vehicles, renewable energy storage systems, and other high-performance battery setups where efficient energy use and long lifespan are priorities. Here's a breakdown of its relevance

1. Enhanced Battery Lifespan

Issue: In lithium-ion battery packs, cells can become imbalanced due to differences in capacity, internal resistance, or aging, causing some cells to charge and discharge faster than others. Solution: Active balancing actively transfers energy from higher-charged cells to lower-charged ones, keeping the cells within a closer state of charge. This balancing process minimizes stress on individual cells and leads to a more even wear pattern across the pack, extending the battery lifespan.

DOI:10.15680/IJMRSET.2025.0806167

ISSN: 2582-7219 | www.ijmrset.com | Impact Factor: 8.206 | ESTD Year: 2018 |



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

2. Improved Energy Efficiency

Issue: Passive balancing, a simpler method, dissipates excess energy from overcharged cells as heat, leading to energy waste and thermal management issues. Solution: Active balancing preserves energy by redistributing it, which reduces energy loss and makes the system more efficient. This is especially relevant in high-energy-demand applications, as it allows the full capacity of the battery to be used effectively.

II. LITERATURE SURVEY

Active cell balancing for a 2s lithium-ion battery pack using a flyback converter and push-pull converter. Kuzhivila Pannikottu Nivya, K Deepa 2021

The paper explains the 2 active cell balancing methods in detail, which helped us understand and simulate cell balancing using a flyback converter in mat lab Simulink.

Simulated Solar Assisted Battery Management System with Fuzzy Temperature Control Flyback Converter Active Cell Balancing Circuit Coulomb Counting SoC Estimation Method using MATLAB Simulink IEEE 2020

The paper explains and shows various other functions of BMS and estimation SOC and explains the feasibility of active cell balancing for solar panels battery storage.

Active Cell Balancing Algorithms in Lithium-ion Battery (master's thesis in science) Bowein Jiang 2019

The thesis elaborates and explains the need of BMS, battery modeling, the types of cells balancing and various other methods of active cell balancing.

Enhanced Switching Pattern to Improve Cell Balancing Performance in Active Cell Balancing Circuit using Multi-winding Transformer 2020 IEEE

The paper explains active cell balancing using a multi-winding flyback converter and various other charge balancing method types such as "module to cell" balancing, "cell to cell distributed" balancing and "cell to cell shared" balancing techniques.

Aim

"Active cell balancing is a more complex balancing technique that redistributes charge between battery cells during the charge and discharge cycles, thereby increasing system run time by increasing the total useable charge in the battery stack, decreasing charge time compared with passive balancing, and decreasing heat "

Problem Statement

As the demand for electric vehicles (EVs), renewable energy storage systems, and portable electronics continues to rise, the efficiency, longevity, and safety of lithium-ion (Li-ion) batteries are of paramount importance. One of the key challenges in maximizing the performance of Li-ion batteries is ensuring that all individual cells within a battery pack are maintained at a consistent state of charge (SOC). Imbalances in cell voltage or capacity can lead to reduced overall battery life, suboptimal performance, or even safety hazards such as overheating or thermal runaway. Cells to lower-charged ones in real time, using efficient power electronic circuits and control algorithms."

Objective:

"To design and implement an active battery balancing system for lithium-ion battery packs that enhances energy efficiency, maximizes usable capacity, and extends battery life by redistributing charge from higher-charged cells to lower-charged ones in real time, using efficient power electronic circuits and control algorithms."

III. PROPOSED METHODOLOGY

Detailed Methodology:

1. Cell Monitoring:

Continuously monitor the voltage and SoC of each cell in the battery pack.

This can be done using sensors connected to each cell or by using algorithms to estimate SoC from current and voltage data.



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

2. DC-DC Converter:

Employ a DC-DC converter, such as a buck converter, to facilitate charge transfer between cells.

The buck converter's output voltage is adjusted based on the voltage difference between the cells, ensuring charge flow from overcharged to undercharged cells.

3. Switch Control:

Use a pair of MOSFET switches (or similar solid-state switches) for each cell.

One switch enables charging, and the other enables discharging.

An algorithm controls these switches, turning them on or off based on the comparison of cell voltages and SoC with the average.

4. Algorithm:

An algorithm is developed to determine which cells need to be charged or discharged.

The algorithm typically involves comparing individual cell voltages and SoC with the average values and triggering the switches accordingly.

The algorithm can be implemented in a microcontroller or other controller.

5. Charge Transfer:

When the algorithm determines that a cell needs to be charged, the charging switch for that cell is turned on, and the discharging switch for the overcharged cell is activated.

The buck converter facilitates the transfer of charge from the overcharged cell to the undercharged cell.

This process continues until all cells have the same SoC.

Example Implementation:

A buck converter with a pair of MOSFET switches for each cell in a series-connected lithium-ion battery pack.

An algorithm that compares the cell voltages and SoC with the average values.

When a cell's SoC is lower than the average, the algorithm turns on the charging switch for that cell and the discharging switch for an overcharged cell.

The buck converter transfers charge from the overcharged cell to the undercharged cell, thus balancing the pack.

Benefits of Active Cell Balancing:

Increased battery life and efficiency.

Improved battery performance, especially in applications with high power demands.

Reduced risk of thermal runaway and other safety issues.

IV. FUNCTIONAL REQUIREMENT

1.ARDUINO UNO: -

Controls the balancing process, monitors cell voltages, and activates balancing circuits. MOSFETs

2.18650 Li-ion cells: -

Typically used for the battery pack to be balanced. Power Supply:

3 MOSFET

MOSFET stands for Metal Oxide Silicon Field Effect Transistor or Metal Oxide Semiconductor Field Effect Transistor. This is also called IGFET meaning Insulated Gate Field Effect Transistor. The FET is operated in both depletion and enhancement modes of operation.

4 CAPACITORS

A capacitor is a device that stores electrical energy in an electric field. It is a passive electronic component with two terminals.

A capacitor works on the principle that the capacitance of a conductor shows increase when an earthed conductor is brought near it

5 VOLTAGE MEASUREMENT

this block measures the voltages and currents specified in the Measurements parameter of Simscape



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

Electrical Specialized Power Systems blocks in your model. Choosing voltages or currents through the Multimeter block is equivalent to connecting an internal voltage or current measurement block inside your block

V. SYSTEM DESIGN

Block Diagram




Figure 1.1: Block Diagram

Figure 1.2 ARDUINO



Figure 1.3 LCD Display 16*2

The term LCD stands for liquid crystal display. It is one kind of electronic display module used in an extensive range of applications like various circuits & devices like mobile phones, calculators, computers, TV sets, etc. These displays are mainly preferred for multi-segment light-emitting diodes and seven segments. The main benefits of using this module are inexpensive; simply programmable, animations, and there are no limitations for displaying custom characters, special and even animations,

- Digital I/O Pins: 14
- PWM Pins: 6 (Pin # 3, 5, 6, 9, 10 and 11)
- Analog Input Pins: 6
- DC Current per I/O Pin: 20 mA
- DC Current for 3.3V Pin: 50 mA
- Size: 68.6 mm x 53.4 mm
- Weight: 25 g

]



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

The microcontroller is an embedded computer chip that controls most of the electronic gadgets and appliances that people use on a daily basis, right from mobile phones, washing machines to anti-lock brakes in cars. The microcontroller was introduced in the electronics industry with the purpose of making our tasks easy that come with even a remote connection with automation in any way.

Uno is a microcontroller board based on 8-bit ATmega328P microcontroller. Along with ATmega328P, it consists other components such as crystal oscillator, serial communication, voltage regulator, etc. to support the microcontroller. The Arduino Uno comes with USB interface, 6 analogue input pins, 14 I/O digital ports that are used to connect with external electronic circuits. Out of 14 I/O ports, 6 pins can be used for PWM output. It allows the designers to control and sense the external electronic devices in the real world



Figure 1.3 Lithium Battery

A lithium-ion or Li-ion battery is a type of rechargeable battery that uses the reversible intercalation of Li+ ions into electronically conducting solids to store energy. In comparison with other commercial rechargeable batteries, Li-ion batteries are characterized by higher specific energy, higher energy density, higher energy efficiency, a longer cycle life, and a longer calendar life. Also noteworthy is a dramatic improvement in lithium-ion battery properties after their market introduction in 1991; over the following 30 years, their volumetric energy density increased threefold while their cost dropped tenfold. In late 2024 global demand passed 1 terawatt-hour per year, while production capacity was more than twice that.

REFERENCES

- [1] Debadyuti Banerjee* (Modern Institute of Engineering & Technology), Anirban Giri (Modern Institute of Engineering & Technology), Shib Sankar Saha (Kalyani Government Engineering College).
- [2] Feng Chen1, Jun Yuan1, Chaojun Zheng1, Canbo Wang1, Zhan Li2 and Xunwei Zhou3,* 1State Grid Zhejiang Electric Power Company, Ltd., Hangzhou, 310007, China 2College of Electrical Engineering, Zhejiang University, Hangzhou, 310027, China 3Hangzhou Xieneng Technology Co., Ltd., Hangzhou 310000, China *Corresponding author
- [3] International Journal of Power Electronics and Drive System (IJPEDS) \bot 571 Vol. 11, No. 2, June 2020, pp. 571~579 ISSN: 2088-8694, DOI: 10.11591/ijpeds.v11.i2.pp571-579
- [4] Active Cell Balancing Approach for Efficient Battery Management System Aakriti Sharma1, Anusha Adhikari2*, Bibek Adhikari3, Pratik Pandey4, Indraman Tamrakar
- [5] Active Cell Balancing in Battery Packs by: Stanislav Arendarik Rožnov pod Radhoštem, Czech Republic
- [6] Performance comparison of active balancing techniques for lithium-ion batteries Author links open overlay panelFederico Baronti, Roberto Roncella, Roberto Saletti
- [7] Samadani E, Mastali M, Farhad S, Fraser RA, Fowler M. Li-ion battery performance and degradation in electric vehicles under different usage scenarios. *Int. J. Energy Res.* 2016; **40**(3): 379-392.
- [8] Shang Y, Zhu C, Fu Y, et al. An integrated heater equalizer for lithium-ion batteries of electric vehicles. *IEEE Trans. Ind. Electron.* 2018; **66**(6): 4398-4405.



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

[9] Huakai Z, Wang Y. Active battery equalization method based on redundant battery for electric vehicles. *IEEE Trans. Veh. Technol*, 2019

[10] Gallardo-Lozano J, Romero-Cadaval E, Milanes-Montero MI, Guerrero-Martinez MA. A novel active battery equalization control with on-line unhealthy cell detection and cell change decision. *J Power Sources*. 2015; **299**: 356-370.

[11] Uno M, Tanaka K. Single-switch multioutput charger using voltage multiplier for series-connected lithium-ion battery/supercapacitor equalization. *IEEE Trans. Ind. Electron.* 2013; **60**(8): 3227-3239.

[12]Ye Y, Cheng KWE, Fong YC, Xue X, Lin J. Topology, modeling, and design of switched-capacitor-based cell balancing systems and their balancing exploration. *IEEE Trans Power Electron*. 2017; **32**(6): 4444-4454.

[13]Diao W, Xue N, Bhattacharjee V, Jiang J, Karabasoglu O, Pecht M. Active battery cell equalization based on residual available energy maximization. *Appl Energy*. 2018; **210**: 690-698.

[14] Schaef C, Din E, Stauth JT. A hybrid switched-capacitor battery management IC with embedded diagnostics for seres-stacked li-ion arrays. *IEEE J. Solid State Circuits*. 2017; **52**(12): 3142-3154

[15]Cui X, Shen W, Zhang Y, Hu C. A fast multi-switched inductor balancing system based on a fuzzy logic controller for lithium-ion battery packs in electric vehicles. *Energies*. 2017; **10**(7): 1034..

[16]Lee SW, Lee KM, Choi YG, Kang B. Modularized design of active charge equalizer for li-ion battery pack. *IEEE Trans. Ind. Electron.* 2018; **65**(11): 8697-8706









INTERNATIONAL JOURNAL OF

MULTIDISCIPLINARY RESEARCH IN SCIENCE, ENGINEERING AND TECHNOLOGY

| Mobile No: +91-6381907438 | Whatsapp: +91-6381907438 | ijmrset@gmail.com |