



International Journal of Multidisciplinary Research in Science, Engineering and Technology

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)



Impact Factor: 8.206

Volume 9, Issue 4, April 2026



A Comparative Survey of Handwritten Digit Recognition Methods

Vijay Pratap Singh¹, Dheeraj Chillar²

P.G. Student, Department of CSE, Sat Kabir Institute of Technology and Management, Ladrawan, Haryana, India¹

Director, Sat Kabir Institute of Technology and Management, Ladrawan, Haryana, India²

ABSTRACT: Handwritten digit recognition is a fundamental problem in the fields of Computer Vision and Pattern Recognition, with widespread applications in banking, postal services, document processing, and automated data entry systems. Over the years, numerous techniques have been developed to address the challenges associated with variability in handwriting styles, noise, and distortions. Early approaches relied on traditional machine learning methods, such as k-Nearest Neighbors (k-NN) and Support Vector Machines (SVM), as well as handcrafted feature extraction techniques. However, these methods were limited in their ability to generalize across diverse datasets. With the advancement of Deep Learning, particularly Convolutional Neural Networks (CNN), significant improvements in recognition accuracy and robustness have been achieved. CNN-based models automatically learn hierarchical features from raw image data, eliminating the need for manual feature engineering. Benchmark datasets such as MNIST and EMNIST have played a crucial role in evaluating and comparing different approaches.

KEYWORDS: Handwritten Digit Recognition, Convolutional Neural Network (CNN), Deep Learning

I. INTRODUCTION

Handwritten digit recognition is a significant research area within Computer Vision and Pattern Recognition, owing to its wide range of applications in banking systems, postal services, document digitization, and automated data entry. The ability to accurately interpret handwritten digits remains a challenging task due to variations in writing styles, differences in stroke thickness, noise, and distortions in input images. Over the years, researchers have proposed various approaches to address these challenges, ranging from traditional machine learning techniques to advanced deep learning models.

Early studies focused on classical machine learning algorithms such as SVM, k-NN, and Random Forests (RF), which relied heavily on handcrafted feature extraction methods. These approaches achieved moderate success but were limited in handling complex variations in handwritten data. According to Yurii Chyehkarov et al. [1], traditional models such as SVM and k-NN achieve reasonable accuracy but struggle to generalize across diverse handwriting styles. Similarly, Shrivastava A. et al. [2] reviewed multiple machine learning techniques and highlighted their limitations in feature representation and scalability.

With the advancement of Deep Learning, particularly Convolutional Neural Networks, significant improvements have been achieved in handwritten digit recognition. CNN-based models automatically learn hierarchical features from raw pixel data, eliminating the need for manual feature engineering. Kalbhor S.R. and Deshpande A.M. [3] demonstrated that CNNs outperform traditional machine learning methods in terms of accuracy and robustness. Furthermore, Pashine S. et al. [4] compared machine learning and deep learning techniques and concluded that deep learning models provide superior performance due to their ability to handle complex data patterns.

Recent research has focused on improving accuracy and developing novel techniques for digit recognition. Ahmed S.S. et al. [5] proposed an advanced deep learning-based method that enhances recognition performance by improving feature extraction and optimization. Additionally, Essam F. et al. [6] explored various machine learning approaches and emphasized the importance of preprocessing and feature selection in improving model accuracy. The use of benchmark datasets, such as MNIST, has played a crucial role in evaluating and comparing different models, as highlighted by Gope B. et al. [7], who demonstrated the effectiveness of machine learning models on standardized datasets.



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

Despite significant progress, challenges such as domain variability, noise, and real-time implementation remain open research problems. This survey paper aims to provide a comprehensive overview of existing techniques for handwritten digit recognition, analyze their strengths and limitations, and highlight future research directions to improve system performance and applicability.




Figure 1: Handwritten Digits Recognition through CNN Model

Figure 2 illustrates the complete workflow of a handwritten digit recognition system, starting from data acquisition to final prediction. In the first stage, data acquisition, handwritten digit images are collected from standard datasets such as MNIST or EMNIST, which provide labeled training and evaluation samples. The second stage, preprocessing, prepares the raw input images for analysis by applying operations such as grayscale conversion, noise removal, resizing, normalization, and binarization. These steps ensure that the input images are standardized (typically 28x28 pixels) and suitable for feature extraction.

In the third stage, feature representation, two approaches are highlighted. Traditional machine learning methods rely on handcrafted features such as Histogram of Oriented Gradients (HOG), edges, contours, and statistical descriptors. In contrast, deep learning methods automatically learn features through multiple layers of a Convolutional Neural Network (CNN), capturing both low-level and high-level patterns in the data. The fourth stage, classification, includes traditional classifiers such as SVM, k-NN, and Random Forests, deep learning models such as CNNs and deep neural networks, and advanced hybrid methods such as CNN-SVM and quantum-inspired algorithms. These models classify the input digit based on extracted features. In the output stage, the system produces the recognized digit along with a confidence score indicating the reliability of the prediction. Additional performance metrics such as accuracy, precision, recall, and F1-score are used to evaluate the effectiveness of the system. Overall, the figure provides a comprehensive overview of the end-to-end process of handwritten digit recognition, integrating preprocessing, feature extraction, classification, and evaluation.




Figure 2: General Steps of Digit Detection



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

II. RESEARCH BACKGROUND

Handwritten digit recognition has evolved significantly over the past few decades, transitioning from traditional neural network approaches to advanced hybrid and deep learning models. Early foundational work by S. Knerr et al. [8] demonstrated the use of single-layer neural networks for digit recognition, marking one of the earliest successful attempts in this domain. These initial models laid the groundwork for future developments but were limited in their ability to handle complex variations in handwriting styles.

With the advancement of machine learning, various algorithms such as Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), and Random Forests were explored for digit classification. A. Gattal et al. [9] introduced feature-based approaches using orientation-based image features and background information, highlighting the importance of feature extraction in improving recognition accuracy. Additionally, Y. Wang et al. [10] proposed a novel approach based on the Quantum k-Nearest Neighbor algorithm, demonstrating improved performance by leveraging quantum-inspired distance measures.

Recent studies have increasingly focused on the application of deep learning techniques, particularly Convolutional Neural Networks (CNNs), due to their superior ability to automatically extract hierarchical features from image data. S. Ahlawat et al. [11] demonstrated that CNN-based models significantly improve recognition accuracy compared to traditional methods. Furthermore, hybrid models combining CNNs and SVMs have been proposed to enhance classification performance by integrating feature learning with robust classification techniques [12]. Similarly, D. Hemalatha et al. [13] emphasized the effectiveness of CNNs for image identification and classification, highlighting their adaptability across diverse domains.

In addition to standard datasets, research has also explored digit recognition in different languages and scripts. For instance, P.K. Adhikary et al. [14] investigated handwritten digit recognition for the Dzongkha language, demonstrating the applicability of machine learning techniques across diverse linguistic contexts. Moreover, advancements in deep learning have extended beyond digit recognition to broader applications such as medical image analysis and signal detection, as shown by H. Fujita et al. [25], indicating the versatility and scalability of CNN-based approaches.

III. TRADITIONAL MACHINE LEARNING METHODS FOR DIGIT RECOGNITION

Traditional machine learning approaches for handwritten digit recognition primarily rely on handcrafted feature extraction followed by classification using algorithms such as SVM, k-NN, and RF. In these methods, meaningful features such as edges, contours, pixel intensities, and gradient-based descriptors (e.g., Histogram of Oriented Gradients) are first extracted from input images, and then used as input to classifiers. For instance, studies such as those by Yurii Chychkarov et al. [1] demonstrate that classifiers such as SVM and k-NN can achieve reasonable accuracy on handwritten digit datasets when combined with effective feature engineering. Similarly, A. Gattal et al. [9] utilized orientation-based image features and background information to improve classification performance, emphasizing the importance of feature representation in traditional methods. Additionally, Y. Wang et al. [10] proposed a Quantum k-Nearest Neighbor approach, which enhances the conventional k-NN algorithm by improving similarity measurement techniques.

These methods were widely used due to their simplicity, interpretability, and lower computational requirements compared to deep learning models. However, their performance is highly dependent on the quality of manually designed features, making them less effective in handling variations in handwriting styles, noise, and distortions. Unlike deep learning approaches, traditional methods lack the ability to automatically learn hierarchical representations from raw data, thereby limiting their generalization capabilities. As a result, although traditional machine learning techniques laid the foundation for digit recognition systems, they have largely been replaced by more advanced models such as CNNs, which offer superior accuracy and robustness.

IV. ADVANCED MACHINE LEARNING AND DEEP LEARNING METHODS FOR DIGIT RECOGNITION

With the rapid advancement of computational power and data availability, handwritten digit recognition has significantly evolved through the adoption of advanced machine learning and deep learning techniques. Among these, CNNs have emerged as the most effective approach due to their ability to automatically learn hierarchical feature



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

representations directly from raw image data. Unlike traditional methods, CNNs eliminate the need for manual feature extraction by using multiple layers, such as convolutional, pooling, and fully connected layers, to capture low-level features (edges and textures) and high-level patterns (digit shapes). Studies such as those by S. Ahlawat et al. [12] demonstrate that CNN-based models significantly outperform conventional machine learning techniques in terms of accuracy and robustness. Similarly, Pashine S. et al. [4] highlighted that deep learning approaches provide superior performance by effectively handling complex variations in handwritten data.

In addition to standalone CNN models, hybrid approaches combining deep learning with classical classifiers have also been proposed. For example, S. Ahlawat and A. Choudhary [11] introduced a hybrid CNN-SVM model, where a CNN is used for feature extraction and an SVM for classification, resulting in improved accuracy and generalization. Furthermore, advanced variants of ML techniques, such as the Quantum k-NN method proposed by Y. Wang et al. [15], aim to enhance classification performance by improving similarity measures. Deep learning models have also shown strong adaptability across domains, as emphasized by D. Hemalatha et al. [13], who demonstrated the effectiveness of CNNs for general image classification. Additionally, research by H. Fujita et al. [15] highlights the broader applicability of deep convolutional networks in complex pattern recognition problems, further validating their capability in digit recognition tasks.

V. QUANTUM-INSPIRED ALGORITHMS

In addition to conventional machine learning and deep learning techniques, several advanced and emerging approaches have been explored to further enhance handwritten digit recognition systems. One such direction is the use of quantum-inspired algorithms, where methods like the Quantum k-Nearest Neighbor (QkNN) leverage principles of quantum computing to improve similarity measurement and classification performance. For example, Y. Wang et al. [10] demonstrated that quantum-based approaches can provide improved accuracy and computational efficiency compared to classical k-NN in certain scenarios. Another promising area is the application of feature engineering techniques based on bio-inspired and statistical models, such as orientation-based features and background modeling. A. Gattal et al. [9] utilized oriented Basic Image Features (oBIFs) combined with background information to enhance digit recognition performance, particularly for complex and noisy handwritten inputs.

VI. HYBRID AND ENSEMBLE-BASED APPROACHES

Furthermore, hybrid and ensemble-based approaches have gained attention, combining multiple models or techniques to improve overall system performance. These methods integrate the strengths of different algorithms, such as combining statistical features with learning-based classifiers, to achieve better robustness and accuracy. Research has also explored domain-specific adaptations, such as recognizing digits in different languages and scripts. For instance, P.K. Adhikary et al. [14] developed machine learning-based approaches for Dzongkha handwritten digit recognition, highlighting the importance of adapting recognition systems to diverse linguistic contexts. Additionally, advances in signal processing and pattern analysis have enabled improved preprocessing and feature extraction, which are critical for accurate recognition.

Emerging research directions also include the use of optimization algorithms, evolutionary computing, and transfer learning frameworks to enhance model performance and adaptability. These approaches aim to address challenges such as limited training data, domain variability, and real-time processing requirements. Overall, these advanced techniques extend beyond traditional paradigms and contribute to the development of more efficient, accurate, and scalable handwritten digit recognition systems.

Table 1: Comparison of Digit Recognition Approaches

Parameter	Traditional Machine Learning (ML)	Deep Learning (DL)	Advanced Methods (Hybrid / Quantum / Feature-Based)
Feature Extraction	Manual (handcrafted features like HOG, edges)	Automatic (learned by network)	Combination of manual + learned or novel features
Common Techniques	SVM, k-NN, Random Forest	CNN, Deep Neural Networks	CNN-SVM, Quantum k-NN, oBIFs, Ensemble models
Accuracy	Moderate (80–95%)	High (95–99%+)	Very High (can exceed DL in some)



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

			cases)
Handling Variability	Poor (sensitive to handwriting changes)	Good (learns variations)	Very Good (optimized + adaptive methods)
Computational Cost	Low	High (requires GPU for training)	Moderate to High (depends on method)
Training Time	Short	Long	Moderate to Long
Dependency on Data	Works with small datasets	Requires large datasets	Can work with both (some methods optimize data use)
Generalization Ability	Limited	Strong	Very Strong (especially hybrid models)
Preprocessing Requirement	High	Moderate	Moderate (sometimes advanced preprocessing used)
Interpretability	High (easy to understand)	Low (black-box model)	Moderate (depends on hybrid structure)
Real-Time Performance	Good	Good (after training)	Good (optimized systems)
Flexibility	Limited	Highly flexible	Highly flexible and adaptive

Aspect	Traditional Machine Learning (ML)	Deep Learning (DL)	Advanced / Hybrid / Emerging Methods
Feature Extraction	Manual / Handcrafted	Automatic (Learned by CNN/DNN)	Combination of Handcrafted + Learned / Novel Features
Algorithms / Models	SVM, k-NN, Random Forest, Naive Bayes, etc.	CNN, DNN, ResNet, LeNet, etc.	CNN-SVM, Quantum k-NN, oBIFs, Ensemble Models, Transfer Learning, etc.
Data Requirement	Low to Moderate	High	Moderate to High
Accuracy	Moderate (80% – 95%)	High (95% – 99%+)	Very High (96% – 99%+ or higher)
Interpretability	High	Low (Black-box)	Moderate
Computational Cost	Low	High (Needs GPU for training)	Moderate to High
Strengths	Simple, Fast, Works on small datasets, Easier to implement	High accuracy, Learns complex patterns, Less preprocessing	Better generalization, Robust to noise, Combines advantages of multiple methods
Limitations	Depends on feature engineering, Less robust to variations and noise	Requires large data, More training time, Less interpretable	Complex design, Higher implementation cost, Requires expertise

Figure 3: Comparative Approaches

Figure 3 presents a comparative analysis of three major approaches used in handwritten digit recognition: Traditional Machine Learning (ML), Deep Learning (DL), and Advanced/Hybrid methods. It highlights key aspects, including feature extraction, algorithms, data requirements, accuracy, interpretability, computational cost, strengths, and limitations. In traditional machine learning, feature extraction is performed manually using handcrafted techniques, and classification is performed using algorithms such as SVM, k-NN, Random Forests, and Naïve Bayes. These methods require relatively low data and computational resources but offer only moderate accuracy and are sensitive to variations in handwriting. In contrast, deep learning approaches automatically learn features from data using models like CNN, Deep Neural Networks (DNN), and architectures such as ResNet and LeNet. These methods achieve higher accuracy and better generalization but require large datasets, higher computational power (often GPU-based), and are less interpretable due to their black-box nature. The figure also presents advanced or hybrid methods that combine the strengths of ML and DL techniques. These include models such as CNN-SVM, quantum k-NN, ensemble learning, and transfer learning approaches. Such methods provide very high accuracy and robustness to noise and variability, though they entail increased complexity and implementation costs.



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

DATASETS: The MNIST dataset [16] is one of the most widely used benchmark datasets for handwritten digit recognition. It was created by modifying the original NIST dataset and consists of grayscale images of the digits 0-9. The dataset contains 70,000 images, divided into 60,000 training images and 10,000 testing images, with each image having a fixed size of 28×28 pixels. The digits are centered and normalized, making the dataset clean and consistent for model training. MNIST is widely used for evaluating machine learning and deep learning algorithms because of its simplicity and standardized format. It provides an ideal starting point for beginners and researchers to test classification models such as SVM, k-NN, and (CNNs). Due to its low complexity, many modern models achieve very high accuracy (often above 98%), making it less challenging but still highly valuable for benchmarking and experimentation.

EMNIST Dataset [17]: The EMNIST dataset (Extended MNIST) is an extension of the MNIST dataset that includes not only digits but also handwritten letters. It was developed to provide a more comprehensive dataset for character recognition tasks. EMNIST contains several subsets such as ByClass, ByMerge, Balanced, Letters, and Digits, with a total of over 800,000 images. Like MNIST, EMNIST images are also grayscale and 28×28 pixels, but they include both uppercase and lowercase letters, as well as digits, significantly increasing the complexity of the classification task. EMNIST is particularly useful for developing systems that go beyond digit recognition to full handwritten character recognition. However, due to the increased number of classes and variations, it is more challenging than MNIST and requires more advanced models and training strategies.

Table 2: Comparative Difference Between DATSETS

Feature	MNIST	EMNIST
Data Type	Digits (0–9)	Digits + Letters
Total Images	70,000	800,000+
Difficulty Level	Easy	Moderate to Hard
Use Case	Digit recognition	Character recognition

VII. CONCLUSION

This survey paper presented a comprehensive review of handwritten digit recognition techniques, covering traditional machine learning, deep learning, and advanced hybrid approaches. The study highlighted the evolution of methods from handcrafted feature-based models, such as SVM and k-NN, to powerful deep learning architectures like CNNs, which have significantly improved recognition accuracy and robustness. Benchmark datasets such as MNIST and EMNIST have played a crucial role in evaluating and comparing different approaches, enabling standardized research and performance analysis. The survey also emphasized that while traditional machine learning methods are simple and computationally efficient, they are limited by their dependency on manual feature extraction and lower generalization capability. In contrast, deep learning techniques provide superior performance through automatic feature learning but require large datasets, higher computational resources, and longer training time. Advanced and hybrid approaches, including CNN-SVM, quantum-inspired algorithms, and ensemble methods, further enhance performance by combining the strengths of multiple techniques, although they introduce additional complexity and implementation challenges. Despite significant advancements, several challenges remain, including handling variations in handwriting styles, noise, domain differences between training and real-world data, and scalability to multi-digit and multilingual recognition. Future research should focus on improving model generalization, reducing computational complexity, and developing robust systems capable of real-time deployment across diverse applications. Overall, handwritten digit recognition continues to be an active and evolving research area, with ongoing innovations contributing to more accurate, efficient, and practical recognition systems.

REFERENCES

- [1] Chychkarov, Y., Serhienko, A., Syrmamiikh, I. and Kargin, A., 2021. Handwritten Digits Recognition Using SVM, KNN, RF and Deep Learning Neural Networks. CMIS, 2864, pp.496-509.
- [2] Shrivastava, A., Jaggi, I., Gupta, S. and Gupta, D., 2019, October. Handwritten digit recognition using machine learning: A review. In *2019 2nd international conference on power energy, environment and intelligent control (PEEIC)* (pp. 322-326). IEEE.
- [3] Kalbhor, S.R. and Deshpande, A.M., 2018, May. Digit recognition using machine learning and convolutional neural network. In *2018 2nd International Conference on Trends in Electronics and Informatics (ICOEI)* (pp. 604-609). IEEE.



International Journal of Multidisciplinary Research in Science, Engineering and Technology (IJMRSET)

(A Monthly, Peer Reviewed, Refereed, Scholarly Indexed, Open Access Journal)

- [4] Pashine, S., Dixit, R. and Kushwah, R., 2021. Handwritten digit recognition using machine and deep learning algorithms. arXiv preprint arXiv:2106.12614.
- [5] Ahmed, S.S., Mehmood, Z., Awan, I.A. and Yousaf, R.M., 2023. A novel technique for handwritten digit recognition using deep learning. *Journal of Sensors*, 2023(1), p.2753941.
- [6] Essam, F., Samy, H. and Wagdy, J., 2023. Mlhandwrittenrecognition: Handwritten digit recognition using machine learning algorithms. *Journal of Computing and Communication*, 2(1), pp.9-19.
- [7] Gope, B., Pande, S., Karale, N., Dharmale, S. and Umekar, P., 2021, January. Handwritten digits identification using mnist database via machine learning models. In *IOP conference series: materials science and engineering* (Vol. 1022, No. 1, p. 012108). IOP Publishing.
- [8] Knerr, S., Personnaz, L. and Dreyfus, G., 1992. Handwritten digit recognition by neural networks with single-layer training. *IEEE Transactions on neural networks*, 3(6), pp.962-968.
- [9] Gattal, A., Djeddi, C., Chibani, Y. and Siddiqi, I., 2016, April. Isolated handwritten digit recognition using oBIFs and background features. In *2016 12th IAPR Workshop on Document Analysis Systems (DAS)* (pp. 305-310). IEEE.
- [10] Wang, Y., Wang, R., Li, D. et al. Improved Handwritten Digit Recognition using Quantum K-Nearest Neighbor Algorithm. *Int J Theor Phys* 58, 2331–2340 (2019).
- [11] Ahlawat, S., Choudhary, A., Nayyar, A., Singh, S. and Yoon, B., 2020. Improved handwritten digit recognition using convolutional neural networks (CNN). *Sensors*, 20(12), p.3344.
- [12] Ahlawat, S. and Choudhary, A., 2020. Hybrid CNN-SVM classifier for handwritten digit recognition. *Procedia Computer Science*, 167, pp.2554-2560.
- [13] Hemalatha, D. and Begum, A., 2021. Image Identification and Classification Using CNN. *Turkish Journal of Computer and Mathematics Education*, 12(9), pp.226-230.
- [14] Adhikary, P.K., Dadure, P., Saha, P. and Pakray, P., 2023. Dzongkha handwritten digit recognition using machine learning techniques. *Procedia Computer Science*, 218, pp.2350-2358.
- [15] Fujita, H. and Cimr, D., 2019. Computer aided detection for fibrillations and flutters using deep convolutional neural network. *Information Sciences*, 486, pp.231-239.
- [16] <https://www.kaggle.com/datasets/marvinluckianto/mnist-dataset>
- [17] <https://www.kaggle.com/datasets/crawford/emnist>



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF MULTIDISCIPLINARY RESEARCH IN SCIENCE, ENGINEERING AND TECHNOLOGY

| Mobile No: +91-6381907438 | Whatsapp: +91-6381907438 | ijmrset@gmail.com |

www.ijmrset.com